CB517A
HP Printer LaserJet P4515xm

This file was downloaded from here

Product Description
HP Printer LaserJet P4515xm

Specifications on this product range

Print speed (black, normal quality, A4)	Up to 60 ppm
Print quality (black, best quality)	Up to 1200 x 1200 dpi
Recommended monthly page volume	5000 to 20000
Duty cycle (monthly, A4)	Up to 275000 pages
Duplex print options	Automatic (standard)
Maximum number of paper trays	6
Maximum input capacity (sheets)	Up to 3600
Maximum output capacity (sheets)	Up to 1100
Network ready	Standard

Print technology	Monochrome Laser
Print speed (black, normal quality, A4)	Up to 60 ppm

First page out (black, A4)	< 8.5 sec (from ready mode)
Processor speed	540 MHz
Processor type	Motorola ColdFire® V5x
Print quality (black, best quality)	Up to 1200 x 1200 dpi
Duty cycle (monthly, A4)	Up to 275000 pages
Recommended monthly page volume	5000 to 20000

Standard paper trays	3
Maximum number of paper trays	6
Media types supported	Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), envelopes, labels, cardstock, transparencies
Standard input capacity (sheets)	Up to 1100
Maximum output capacity (sheets)	Up to 1100
Duplex print options	Automatic (standard)

Paper handling standard/input	100-sheet multipurpose tray, two 500-sheet input trays
Paper handling optional/input	Optional 500-sheet input tray, optional 1500-sheet input tray (up to 3 additional trays for up to 3600-sheet input capacity), two-sided printing accessory, optional 75-sheet envelope feeder
Paper handling standard/output	100-sheet rear output bin, 500-sheet top output bin, 500-sheet 5-bin mailbox
Paper handling optional/output	Optional 500-sheet stacker, optional 500-sheet stapler/stacker
Standard media sizes	A4, A5, B5 (JIS), 16K, Dpostcard (JIS), Executive (JIS), envelope (DL ISO, C5 ISO, B5 ISO)
Custom media sizes	Multipurpose Tray: 76 x 127 to 216 x 356 mm; Tray 2 and optional 500-sheet tray: 148 x 210 to 148 x 356 mm; Custom Media Cassette: 102 x 148 to 170 x 282 mm
Media weights by paper path	Multipurpose tray 1: 60 to 200 g/m², standard cassette (Tray 2): 60 to 120 g/m², optional custom media cassette (Tray 2): 60 to 120 g/m², standard cassette (Tray 3): 60 to 120 g/m², optional envelope feeder: 75 to 105 g/m², optional 500-sheet trays: 60 to 120 g/m², optional 1500-sheet high-capacity input tray: 60 to 120 g/m², optional two-sided printing accessory: 60 to 120 g/m²

Standard connectivity	Embedded Jetdirect (Gigabit Ethernet) print server, 1 Hi-Speed USB 2.0, 1 EIO slot, 1 external and 2 internal Host USB 2.0-like ports for 3rd party connection
Optional connectivity	HP Jetdirect EIO internal print servers, HP Jetdirect external print servers, HP wireless print servers, HP Jetdirect EIO connectivity card (for USB, serial, LocalTalk), Bluetooth® wireless
Compatible operating systems	Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003; Certified for Windows Vista®; Mac OS X v10.2, v10.3 or higher
Compatible network operating systems	Via an HP Jetdirect print server: Microsoft® Windows® 2000, Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP, and Windows Vista®); Novell® 5.1 and later; Mac OS X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later; SUSE Linux 8.x and later; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 and later (SPARC® systems only); IBM® AIX 3.2.5 and later; MPE-iX; Citrix® MetaFrame Server; Microsoft® Windows® Terminal Services
Minimum system requirements	Microsoft® Windows® 2000: 133 MHz processor, 64 MB RAM, CD-ROM drive; Microsoft® Windows® XP Home and Professional: 233 MHz processor, 64 MB RAM, CD-ROM drive; Microsoft® Windows® Server 2003: 550 MHz processor, 128 MB RAM (standard edition), 220 MB of free hard disk space for Microsoft® Windows®, 1 GHz processor, 512 MB RAM (Windows Vista® Ready, check user guide for minimum hard drive space); CD-ROM drive or Internet connection, IEEE 1284-compliant bidirectional parallel port, USB (compatible with USB 1.1 or 2.0 specifications)
Control panel	2.29 x 5.33 cm 4-Line LCD display, 3 light-emitting diode (LED) indicator lights (Ready, Data, Attention), buttons (10 numeric keys, Information, Return, Stop/Cancel, OK, Toggle up/down)
Power consumption	910 watts maximum (active/printing), 20 watts maximum (ready), 15 watts maximum (sleep), 0 watts maximum (off). Typical electricity consumption (TEC) 5.049 kWh/Week
Power requirements	Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz)
Dimensions (W x D x H)	419 x 508 x 977 mm
Weight	41.91 kg
Operating temperature range	15 to 32.5° C
Recommended operating temperature range	10 to 32° C

Energy Star certified	Yes
Software included	Print drivers and installation software on CD-ROM: HP PCL 5e, HP PCL 6, Postscript, Postscript Printer Description files, HP LaserJet Utility (Mac), Macintosh software
What's in the box	Printer, right-angled power cord, control panel overlay, software and documentation on CD-ROM, print cartridge, Getting Started Guide, support flyer
Warranty	One year on-site warranty. Optional HP Care Pack services available. Warranty and support options vary by product, country and local legal requirements.

© 2002 - 2011 ComXpert International CC

Accuracy of information is not guaranteed.
Images are a reference and may differ from actual product.
E&OE. Terms and conditions apply.

Full site: http://www.comx.co.za/
Mobile site: http://m.comx.co.za/
Enhanced mobile site: http://touch.comx.co.za/
Facebook: http://www.facebook.com/pages/ComX-Computers/130126582879
Twitter: http://twitter.com/comxcomputers